



SETTING RINGS, METRIC

Used to set internal micrometers and three-point micrometers to zero.

► Inspection report included.

A Uncertainty of engraved diameter

B Cylindricity



▲ 00944010

Order number	Diameter (mm)	A (mm)	B (mm)
00944004	6	± 0,0015	0,0010
00944005	8	± 0,0015	0,0010
00944006	10	± 0,0015	0,0010
00944008	16	± 0,0015	0,0010
00944010	25	± 0,0015	0,0010
00944012	40	± 0,0015	0,0010
00944014	62	± 0,0015	0,0015
00944017	87	± 0,0015	0,0015

SETTING RINGS, INCH

Used to set internal micrometers and three-point micrometers to zero.

► Inspection report included.

A Uncertainty of engraved diameter

B Cylindricity



▲ 00954009

Order number	Diameter (in)	A (in)	B (in)
00954003	0.275	± 0.00006	0.00004
00954004	0.350	± 0.00006	0.00004
00954006	0.500	± 0.00006	0.00004
00954007	0.650	± 0.00006	0.00004
00954009	1.000	± 0.00006	0.00004
00954011	1.600	± 0.00006	0.00004
00954013	2.500	± 0.00006	0.00006
00954016	3.500	± 0.00006	0.00006