

# AGD2 DIAL INDICATORS, 58MM



- ▀ Measuring travel 1 in.
- ▀ Continuous reading 0 ÷ 100 in.
- ▀ Dial diameters from 2 up to 1/4 in.
- ▀ Revolution counter.
- ▀ Tolerance pointers.
- ▀ Central lug back.
- ▀ Carbide contact point.
- ▀ AGD2 clamping shank with diameter to 0.375 in.
- ▀ Supplied in a case made of industrial plastic with inspection report.



▲ 01424010



▲ 01424011



▲ 01424012

Order number	Measuring span	Scale division	Travel per revolution	Dial face	Movement
01424010	1 in	0.001 in	0.100 in	white	
01424011	1 in	0.001 in	0.100 in	black	
01424012	0.5 in	0.0005 in	0.05 in	white	Ruby - Shockproof

Maximum permissible errors (MPE)			
Scale division 0.001 / 0.0005	Measuring span		
	0.5 in	1 in	
Repeatability	0.20 scale division	0.20 scale division	
Hysteresis	0.33 scale division	0.33 scale division	
Precision			
1 revolution	1.00 scale division	1.00 scale division	
First revolution up to 2,5	1.00 scale division	1.00 scale division	
> 2,5 thru 10 revolutions	3.00 scale division	2.00 scale division	

