

## Micrometers with One Spherical Measuring Face

Measure wall thickness of tubing.

### Models MICROMASTER



	mm	in
06030079	0 ÷ 30	0 ÷ 1.2
06030080	25 ÷ 50	1 ÷ 2

### Model ETALON



	mm
071115940	0 ÷ 25

## Micrometers with Two Spherical Measuring Faces

Rounded Measuring faces on anvil and spindle for measuring concave surfaces of workpieces, e.g. ball-bearing guides or walls of tubing.

### Models MICROMASTER



	mm	in
06030081	0 ÷ 25	0 ÷ 1
06030082	20 ÷ 50	0.8 ÷ 1.9
06030083	45 ÷ 75	1.8 ÷ 2.9
06030084	70 ÷ 100	2.8 ÷ 3.9



DIN 863 T3 (Style D1)

MICROMASTER: 0,001 mm or 0.00005 in

ETALON: 0,002 mm

Anvil: tungsten carbide (MICROMASTER) or titanium carbide hard-coating (ETALON). Tungsten carbide spindle.

Anvil with a 3,5 mm spherical face (MICROMASTER) or a 3,25 mm one (ETALON). Spindle with a flat measuring face.

Max. 10 N

RS 232 on MICROMASTER

Other technical data on MICROMASTER: see page C-3.

Plastic case

Identification number

Inspection report with a declaration of conformity



DIN 863 T3 (Style D1)

0,001 mm or 0.00005 in

Tungsten carbide

Spherical, 3,5 mm radius.

Max. 10 N

Additional technical data: see page C-3.

Plastic case

Identification number

Inspection report with a declaration of conformity