

Micrometers for Thread Measurement

Used for pitch diameter inspection – Anvil with adjustable holder for mounting a measuring insert with prismatic faces – Fine screw adjustment and locking device – Spindle has a fixing bore for a cone-shaped measuring insert.

Models MICROMASTER AC



No		
	mm	in
06030062	0 ÷ 25	0 ÷ 1
06030063	25 ÷ 50	1 ÷ 2
06030064	50 ÷ 75	2 ÷ 3
06030065	75 ÷ 100	3 ÷ 4
06030066	100 ÷ 125	4 ÷ 5
06030067	125 ÷ 150	5 ÷ 6

Important

Measuring Inserts and setting standards must be ordered separately.

Models ISOMASTER AC



No	
	mm
00210001	0 ÷ 25
00210002	25 ÷ 50
00210003	50 ÷ 75
00210004	75 ÷ 100

Important

Measuring Inserts and setting standards must be ordered separately.

- ✓
- DIN 863 T3 (Style D18)
- 0,001 mm
0.00005 in
- Metric/Inch conversion
- 30 mm measuring span
- Max. 10 N
- RS 232
- Additional technical data on page C-3
- Plastic case
- Identification number
- Inspection report with a declaration of conformity

- ✓
- DIN 863 T3 (Style D 18)
NF E 11-090
- 0,01 mm
- 0,5 mm
- Max. 10 N
- Plastic case
- Identification number
- Declaration of conformity