


Interchangeable Thread Inserts for TESA Micrometers Series AC

With measuring faces specially designed for checking pitch diameters.



Hardened steel



Fixing rod:
3,5 mm dia.,
15,5 mm long



Supplied in sets
or pairs

No	Pitch in mm	No	Threads per in	No	Threads per in
<i>ISO metric threads 60° flank angle</i>		<i>Whitworth threads 55° flank angle</i>		<i>Unified inch-threads UN, UNC, UNF... 60° flank angle</i>	
00240000	0,4 ÷ 0,5	00250100	60 ÷ 48	00250000	64 ÷ 42
00240001	0,5 ÷ 0,6	00250101	48 ÷ 40	00250001	42 ÷ 25
00240002	0,6 ÷ 0,8	00250102	40 ÷ 32	00250002	25 ÷ 17
00240003	0,8 ÷ 1,0	00250103	32 ÷ 24	00250003	17 ÷ 10
00240004	1,0 ÷ 1,25	00250104	24 ÷ 18	00250004	10 ÷ 6.5
00240005	1,25 ÷ 1,5	00250105	18 ÷ 14	00250005	6.5 ÷ 4
00240006	1,5 ÷ 2,0	00250106	14 ÷ 10	00250006	4 ÷ 2.5
00240007	2,0 ÷ 2,5	00250107	10 ÷ 7		
00240008	2,5 ÷ 3,0	00250108	7 ÷ 4.5		
00240009	3,0 ÷ 4,0	00250109	4.5 ÷ 3		
00240010	4,0 ÷ 5,0				
00240011	5,0 ÷ 6,0				
<i>Set of 12 pairs</i>		<i>Set of 10 pairs</i>		<i>Set of 7 pairs</i>	
00240015	0,4 ÷ 6,0	00250115	60 ÷ 3	00250015	64 ÷ 2.5



Hardened steel



Insulating
sleeve marked
with actual size



Identification
number



Declaration
of conformity

Setting Standards for Screw Thread Micrometers



No	mm	No	in
<i>60° flank angle</i>			
00240501	25	00250501	1
00240502	50	00250502	2
00240503	75	00250503	3
00240504	100	00250504	4
00240505	125	00250505	5
<i>55° flank angle</i>			
00240601	25		
00240602	50		
00240603	75		