



DIN 863 T1
NF E 11-095

0 to 100 mm
resp. 0 to 4 in
with vernier

Tungsten carbide
tipped

≤ 100 mm:
Ø 6,5 mm,
> 100 ≤ 200 mm:
Ø 8 mm

0,5 mm

Max. 10 N

Plastic case

Identification
number

Measuring
range
0 to 100 mm
with inspection report and
declaration of conformity

Measuring
range smaller
than 100 mm
with a declaration of
conformity

ETALON 260 Standard Models with Analogue Indication

The knurled sleeve only needs to be reversed to render the friction drive built into the thimble inactive.



No	mm	mm	µm	µm
071115887	0 ÷ 25	0,002	2	2
071115888	25 ÷ 50	0,002	2	2
071115889	50 ÷ 75	0,002	3	3
071115890	75 ÷ 100	0,002	3	3
071115891	100 ÷ 125	0,01	4	3
071115892	125 ÷ 150	0,01	4	3
071115893	150 ÷ 175	0,01	5	4
071115894	175 ÷ 200	0,01	5	4

No	in	in	µm	µm
071115899	0 ÷ 1	0.0001	2	2
071115900	1 ÷ 2	0.0001	2	2
071115901	2 ÷ 3	0.0001	3	3
071115902	3 ÷ 4	0.0001	3	3



DIN 863 T1
NF E 11-095

0,01 mm

Tungsten carbide
tipped

Ø 6,5 mm

0,5 mm

Max. 10 N

Plastic case

Identification
number

Inspection report
with a declaration of
conformity

ETALON Basic to 0,01 mm



No	mm
00119046	0 ÷ 25
00119047	25 ÷ 50
00119048	50 ÷ 75
00119049	75 ÷ 100

No	mm
00119050	0 ÷ 100

Set of 4 ETALON Basic to 0,01 mm