

TESA DIGICO 400 and 500

- Measuring modes **ABS/REL**.
- Dual LC Display.
- Display rotation through 270°. Same goes for the key functions.
- Mechanical tolerance marks.
- Symbols for both limit values.

Measuring functions and modes

ON – Auto OFF – PRESET mode – Tolerance mode – Data output – Counting sense reversal – Keypad lock – Metric/Inch units – Full RESET.



Combined analogue and numerical display

6-decade LC display field plus minus sign

10 x 5 mm Digit size (H x L)

Resolution to 0,01 mm = ±0,25 mm
Resolution to 0,001 mm = ±0,025 mm

MI or MIE type: metric/inch conversion

Glass scale with incremental divisions, capacitive

≤ 2 m/s

Full-metal housing with front face in polyamide.
Stainless steel plunger.
M2,5 mounting thread for the measuring insert.

RS232, opto-coupled

3V lithium battery, type CR2032

1 year to 2 years

10°C to 40°C

-10°C to 60°C

80%

EN 50081-1
EN 50082-1

Shipping case including one lithium battery 01961000

Identification number

Inspection report with a declaration of conformity

NO	=	mm/in	mm/in	µm	µm	N	g
----	---	-------	-------	----	----	---	---

TESA DIGICO 400

01930240	Digico 405 MI	12,5 / 0.5	0,01 / 0.0005	20	10	< 2	150
01930241	Digico 410 MI	25 / 1	0,01 / 0.0005	20	10	< 2	162

TESA DIGICO 500

01930250	Digico 505 MI	12,5 / 0.5	0,001 / 0.00005	4	2	< 2	150
01930251	Digico 510 MI	25 / 1	0,001 / 0.00005	5	2	< 2	162

TESA DIGICO 505 IP54

01930255	Digico 505 MIE	12,5 / 0.5	0,001 / 0.00005	4	2	< 2	150
-----------------	----------------	------------	-----------------	---	---	-----	-----

