

POWER PANEL



Dual LC display, 128 x 63 mm in size.

• Upper display field for length values (7-segment/sign). Also with symbols for the functions.

• Lower full dot display field for perpendicularity and straightness along with symbols for all operator-controlled function keys.

7-decade display plus minus sign for the measured values.

12,7 x 6,4 mm main display, 6,3 x 4,2 mm auxiliary display.

See opposite

Metric/Inch conversion

Floating zero

PRESET function for entering a given value.

Continuous displaying.

Manual or automatic triggering of data transfer.

Output of predefined inspection reports with headings in 5 languages plus A4 format using an external printer unit.

Via TESA MICRO-HITE

IP40 (IEC 60529)



Control Panel for TESA MICRO-HITE 350 / 600 / 900



00760163

TESA POWER PANEL

Includes a dedicated programme for measuring in 1 and 2 coordinate directions with geometric combination of the measured values. Lets you measure perpendicularity, straightness and squareness. Provides 99 workpiece oriented measurement cycles including 64 features with related limits of size, programmable. Memory capacity for 2500 measured values. Statistical data processing (SPC). Result output via the built-in matrix printer or in A4 format using an external printer unit.



0,0005 / 0,001 / 0,01 / 0,1 mm
0,00002 / 0,0001 / 0,001 / 0,01 / 0,1 in

Accessory for TESA POWER PANEL

04765008 Thermal paper roll, 57 mm wide

