

TESA-HITE 400 / 700



00730043 TESA-HITE 400 height gauge
 Measuring span 415 mm / 16 in
 Application range 0 ÷ 570 mm / 0 ÷ 22 in

00730044 TESA-HITE 700 height gauge
 Measuring span 715 mm / 28 in
 Application range 0 ÷ 870 mm / 0 ÷ 34 in

Each height gauge is supplied with the following standard accessories:

- 00760143** 1 Standard probe insert holder
- 00760227** 1 Standard probe insert with shank and 5 mm dia. ball tip in tungsten carbide
- 00760219** 1 Master piece for establishing the probe constant, nominal dimension to 6,350 mm / 0.2500 in
- 00760226** 1 Electric pump for creating the air-cushion beneath the gauge base, already mounted
- 00760157** 1 Rechargeable battery, 6 V
- 04761054** 1 Mains adapter, 100 ÷ 240 Vac/50 ÷ 60 Hz
- 04761055** 1 Cable EU for mains adapter
- 04761056** 1 Cable US for mains adapter



See table opposite



EN 61326, Class B (with disconnected charger)



Shipping packaging



Identification number



Declaration of conformity



SCS calibration certificate

Technical data

			TESA-HITE 400	TESA-HITE 700
		mm in	415 16	715 28
	With standard accessory	mm in	0 ÷ 570 0 ÷ 22	0 ÷ 870 0 ÷ 34
	With probe insert holder No. 00760057	mm in	0 ÷ 625 0 ÷ 24	0 ÷ 925 0 ÷ 36
	With probe insert holder No. S07001622	mm in	0 ÷ 795 0 ÷ 31	0 ÷ 1095 0 ÷ 43
	With standard accessory	µm in	(2,5+4•L) µm (L in m) (0.0001+0.000004•L) in (L in in)	
	With standard accessory		on flat surfaces: 2δ = <2 µm / <0.0001 in into bores: 2δ = <3 µm / <0.00015 in	
	Frontal, mechanical	µm in	9 0.00035	13 0.0005
		kg	27	32

Standard Accessories for TESA-HITE 400 / 700

